

Mini Converter SDI Distribution



Now you can distribute a single SD or HD-SDI connection to up to 8 different SDI outputs at the same time! You get a true 3G-SDI design with fully re-clocked outputs and automatic switching between all SD and HD formats up to 1080p60. You also get support for all ASI, ancillary and embedded audio formats. Mini Converter SDI Distribution is the perfect SD/HD SDI distribution converter for when you don't need the cost of the Ultra HD model!

NZ\$395

Connections

SDI Video Inputs

1 x SDI Video Input. Switchable between SD, HD and 3G-SDI.

SDI Video Outputs


8 outputs automatically match the SDI video input.

Multi Rate Support

Auto detection of SD, HD or 3G-SDI.

Reclocking

Yes



Standards

SD Video Standards

525i59.94 NTSC, 625i50 PAL

HD Video Standards

720p50, 720p59.94, 720p60, 1080i50, 1080i59.94, 1080i60, 1080p23.98, 1080PsF23.98, 1080p24, 1080PsF24, 1080p25, 1080PsF25, 1080p29.97, 1080PsF29.97, 1080p30, 1080PsF30, 1080p50, 1080p59.94, 1080p60.

2K Video Standards

2K DCI 23.98p, 2K DCI 24p, 2K DCI 25p, 2K DCI 23.98PsF, 2K DCI 24PsF, 2K DCI 25PsF

SDI Compliance

SMPTE 259M, SMPTE 292M,
SMPTE 296M, SMPTE 372M,
SMPTE 424M-B and SMPTE 425M

SDI Video Rates

SDI video connections are switchable
between SD, HD, and DCI 2K.

SDI Video Sampling

4:2:2 and 4:4:4

SDI Audio Sampling

Television standard sample rate
of 48 kHz and 24 bit.

SDI Color Precision

4:2:2 and 4:4:4

SDI Color Space

YUV and RGB


SDI Auto Switching

Automatically detects SD,
HD or 3G-SDI.

ASI Support

Yes

Operating Systems



Mac 10.14 Mojave,
Mac 10.15 Catalina or later.



Windows 8.1 or Windows 10.

Power Requirements

Power Supply

+12V universal power supply included
with international socket adapters for
all countries. Cable tie point.


Power Consumption

4.80 Watts

Operational Voltage Range

12 - 31V DC

Physical Specifications



Environmental Specifications

Operating temperature

0° to 40° C (32° to 104° F)

Storage temperature

-20° to 45° C (-4° to 113° F)

Relative Humidity

0% to 90% non-condensing

What's Included

Mini Converter SDI Distribution

12V universal power supply with international socket adapters

Warranty

3 Year Limited Manufacturer's Warranty.

All items on this website are copyright Blackmagic Design Pty. Ltd. 2020, all rights reserved.

All trademarks are property of their respective owners. MSRP includes GST and excludes shipping costs.

This website uses remarketing services to advertise on third party websites to previous visitors to our site.

You can opt out at any time by changing cookie settings. [Privacy Policy](#)

Blackmagic Design Authorized Reseller